



Specifications Ledvance LED Downlight Performance DN155 14W 1500lm 65D - 830 Warm White | 180mm - IP54 - Dali Dimmable

[View Product](#)

General Information

| | |
|--------------------------|------------------------------------|
| SKU | 238966 |
| EAN | 4058075459298 |
| Brand | Ledvance |
| Manufacturer Name | DL UGR19 DN155 PFM 14W/830 DALI WT |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 14 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |

| | |
|--------------------------|--------------------------------|
| Beam Angle (degree) | 65 |
| Luminous Flux (Lumen) | 1500 |
| Luminous Efficacy (lm/W) | 108 |
| Power factor | >0.90 |
| Installation Depth (mm) | 100 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 155 |
| IP-rating | IP54 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +45 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | Screw terminal, 5-pole |
| Series | DN155 |

Dimensions

Height (mm)

Why Any-lamp?

65

Diameter (mm)

180



Order from the **largest lighting specialist** in Europe



Customised quotation

Sensor Information



Up to **7 years warranty**



Easy return process

Type of sensor

No Sensor