



Specifications Ledvance LED Downlight Performance DN195 Zigbee White 21W 2520lm - 840 Cool White | 220mm - Cutout 195mm

[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 243657 |
| EAN | 4058075459397 |
| Brand | Ledvance |
| Manufacturer Name | DL UGR19 DN195 PFM 21W/840 ZBVR WT LEDV |
| Any Lamp all-in warranty | 3 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wireless connection | Zigbee |
| Lighting Control | Zigbee |
| Wattage | 21 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |

| | |
|--------------------------|--------------------------------|
| Light colour options | Single Color |
| Including bulb | Yes |
| Beam Angle (degree) | 65 |
| Luminous Flux (Lumen) | 2520 |
| Luminous Efficacy (lm/W) | 120 |
| Power factor | >0.90 |
| Installation Depth (mm) | 120 |
| Unified Glare Rating | < 19 - for offices and schools |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 195 |
| IP-rating | IP54 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +45 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Series | DN195 |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 65 |
| Diameter (mm) | 220 |

Why Any-lamp?



Order from the **largest lighting specialist** in Europe



Customised quotation

Sensor Information



Up to **7 years warranty**



Easy return process

| | |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|