



Specifications Noxion LED Downlight
Apollo V2 9-15W 1080-1860lm 60D -
830/840 CCT | 175mm - Cutout
150mm - Emergency 1H

[View Product](#)

General Information

| | |
|--------------------------|----------------------------------------------------------------------------------------------|
| SKU | 250758 |
| EAN | 8719157928793 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Downlight Apollo V2.0 9/12/15W MAX 1860lm 2CCT Cutout Ø150mm Frame Ø175mm + EM1HR |
| Any Lamp all-in warranty | 6 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|----------------------------------|
| Emergency Lighting | 1H Emergency Light |
| Technology | LED Integrated |
| Replaces (Watt) | 30 |
| Wattage | 15 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White, 840 Cool White |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | CCT |
| Beam Angle (degree) | 60 |

| | |
|--------------------------|--------------------------------|
| Luminous Flux (Lumen) | 1860 |
| Luminous Efficacy (lm/W) | 128 |
| Power factor | >0.90 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Series | Apollo |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 108 |
| Diameter (mm) | 175 |

Why Any-lamp?

Sensor Information

 **Order from the largest lighting specialist** in Europe  **Customised quotation**

Type of sensor No Sensor

 **Up to 7 years warranty**  **Easy return process**